

ANACONDA FITTINGS for HIPROJACKET®

IP 54 , -50 °C till +260 °C , NICKEL PLATED BRASS , with special clamprings



ISO straight fitting, male, nickel plated brass



ISO thread size	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
Min. intern diam. mm	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Standard pack. pcs.	50	50	25	10	5	5	4
Article No.	812.016.1	812.020.1	812.025.1	812.032.1	812.040.1	812.050.1	812.063.1



HiproJacket trade size	HJ-06	HJ-10	HJ-14	HJ-18	HJ-21	HJ-26	HJ-32
Article no. clampring	817.512.0	817.516.0	817.520.0	817.526.0	817.535.0	817.540.0	817.550.0

ThermoJacket trade size	TJ-10	TJ-10	TJ-10	TJ-14	TJ-22	TJ-22	TJ-44
Article no. clampring	817.612.0	817.616.0	817.620.0	817.626.0	817.635.0*	817.640.0*	817.650.0*

* Please note that for the bigger sizes ThermoJacket * additional taping (2 layers of hiprosiltape) is needed to obtain a proper pull-out strength.

ISO straight fitting, swivel male, nickel plated brass



ISO thread size	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	-	-
Min. intern diam. mm	10,2	13,9	18,5	23,8	31,8	-	-
Standard pack. pcs.	50	50	25	10	5	-	-
Article No.	813.016.1	813.020.1	813.025.1	813.032.1	813.040.1	-	-



HiproJacket trade size	HJ-06	HJ-10	HJ-14	HJ-18	HJ-21	-	-
Article no. clampring	817.512.0	817.516.0	817.520.0	817.526.0	817.535.0	-	-

ThermoJacket trade size	TJ-10	TJ-10	TJ-10	TJ-14	TJ-22	-	-
Article no. clampring	817.612.0	817.616.0	817.620.0	817.626.0	817.635.0*	-	-

* Please note that for the bigger sizes ThermoJacket * additional taping (2 layers of hiprosiltape) is needed to obtain a proper pull-out strength.

ISO straight fitting, female, nickel plated brass



ISO thread size	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
Min. intern diam. mm	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Standard pack. pcs.	50	50	25	10	5	5	4
Article No.	812.316.1	812.320.1	812.325.1	812.332.1	812.340.1	812.350.1	812.363.1



HiproJacket trade size	HJ-06	HJ-10	HJ-14	HJ-18	HJ-21	HJ-26	HJ-32
Article no. clampring	817.512.0	817.516.0	817.520.0	817.526.0	817.535.0	817.540.0	817.550.0

ThermoJacket trade size	TJ-10	TJ-10	TJ-10	TJ-14	TJ-22	TJ-22	TJ-44
Article no. clampring	817.612.0	817.616.0	817.620.0	817.626.0	817.635.0*	817.640.0*	817.650.0*

* Please note that for the bigger sizes ThermoJacket * additional taping (2 layers of hiprosiltape) is needed to obtain a proper pull-out strength.

ANACONDA fittings for Hiprojacket

These IP 54 fittings have a temperature range of -50°C till +260°C. **Also available with PG and NPT thread sizes.** On demand also available in Stainless Steel (-50°C till +600°C) In case of a cable-hose fitting an IP rate for the switchbox of IP 68 can be obtained. The cable-hose fitting has a temperature range of -40°C till +100°C.

ANACONDA fittings for ThermoJacket.

Because of the IP rate of ThermoJacket is IP 40, these fittings are also IP40. Temperature range from -25°C till +260°C. For temperatures untill +538°C Stainless Steel fittings must be used. **Also available with PG and NPT thread sizes.**

ANACONDA FITTINGS for HIPROJACKET®

IP 54, -50°C till +260°C, NICKEL PLATED BRASS, with special clamprings



ISO 45° fitting, male nickel plated brass



ISO thread size	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
Min. intern diam. mm	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Standard pack. pcs.	50	50	25	10	5	5	4
Article No.	812.416.1	812.420.1	812.425.1	812.432.1	812.440.1	812.450.1	812.463.1

HiproJacket trade size	HJ-06	HJ-10	HJ-14	HJ-18	HJ-21	HJ-26	HJ-32
Article no. clampring	817.512.0	817.516.0	817.520.0	817.526.0	817.535.0	817.540.0	817.550.0

ThermoJacket trade size	TJ-10	TJ-10	TJ-10	TJ-14	TJ-22	TJ-22	TJ-44
Article no. clampring	817.612.0	817.616.0	817.620.0	817.626.0	817.635.0*	817.640.0*	817.650.0*

* Please note that for the bigger sizes ThermoJacket * additional taping (2 layers of hiposiltape) is needed to obtain a proper pull-out strength.

ISO 90° fitting, male, nickel plated brass



ISO thread size	M16x1,5	M20x1,5	M25x1,5	M32x1,5	M40x1,5	M50x1,5	M63x1,5
Min. intern diam. mm	10,2	13,9	18,5	23,8	31,8	36,8	47,8
Standard pack. pcs.	50	50	25	10	5	5	4
Article No.	812.916.1	812.920.1	812.925.1	812.932.1	812.940.1	812.950.1	812.963.1

HiproJacket trade size	HJ-06	HJ-10	HJ-14	HJ-18	HJ-21	HJ-26	HJ-32
Article no. clampring	817.512.0	817.516.0	817.520.0	817.526.0	817.535.0	817.540.0	817.550.0

ThermoJacket trade size	TJ-10	TJ-10	TJ-10	TJ-14	TJ-22	TJ-22	TJ-44
Article no. clampring	817.612.0	817.616.0	817.620.0	817.626.0	817.635.0*	817.640.0*	817.650.0*

* Please note that for the bigger sizes ThermoJacket * additional taping (2 layers of hiposiltape) is needed to obtain a proper pull-out strength.

ANACONDA fittings for HiproJacket

These IP 54 fittings have a temperature range of -50°C till +260°C. **Also available with PG and NPT thread sizes.** On demand also available in Stainless Steel (-50°C till +600°C). In case of a cable-hose fitting an IP rate for the switchbox of IP 68 can be obtained. The cable-hose fitting has a temperature range of -40°C till +100°C.

ANACONDA fittings for ThermoJacket.

Because of the IP rate of ThermoJacket (IP 40), these fittings are also IP40. Temperature range from -25°C till +260°C. For temperatures up to +538°C Stainless Steel fittings must be used. **Also available with PG and NPT thread sizes.**

ALSO AVAILABLE IN COMBINATION WITH THE SPECIAL CLAMPRINGS

PG, NPT THREAD SIZES



CABLE HOSE FITTINGS



STAINLESS STEEL FITTINGS